

# LITHOCHROME<sup>®</sup> Color Hardener, LITHOCHROME<sup>®</sup> Antiquing Release & SCOFIELD<sup>®</sup> Texturetop<sup>®</sup>

## PRODUCT DESCRIPTIONS:

**LITHOCHROME Color Hardener** is a dry-shake colored hardener formulated to be easily incorporated into the surface of freshly placed concrete.

**LITHOCHROME Antiquing Release** is a powdered, colored bond breaker used when imprinting with mat-type texturing or stamping tools.

**SCOFIELD Texturetop** is a trowelable cementitious topping for resurfacing and texturing nonmoving, interior or exterior concrete floors or hardscapes.

**LITHOCHROME<sup>®</sup> Colorwax<sup>™</sup>** curing compound and **COLORCURE<sup>®</sup> Concrete Sealer** are available in matching colors.

## Additional colors available:

A-11 Concrete Gray, 6016 White, 0510 Black.

Some colors are made to order. Check price list for availability, pricing and possible minimum quantities.

*Review Tech-Data Bulletins and MSDS before use. Visit [www.scofield.com](http://www.scofield.com) for the most current versions.*

A53 *Arizona Tan*0266 *Ash White\**1138-S *Blue Smoke+SS*A59 *Beige Cream\**0588 *Blush Beige\**A26 *Brick Red*1139 *Burberry Beige\**A33 *Classic Gray*A27 *Dark Red*A21 *Deep Charcoal*A25 *La Crescenta Brown*3611 *Oyster White\**A65 *Pecan Tan*A57 *Platinum Gray*A24 *Russet*A85 *Muted Green*A50 *Slate Gray*4948 *Smoke Beige\**A51 *Steadman Buff*5183 *Stone Gray\**A29 *Terra Cotta*A28 *Tile Red*5921 *Walnut*5758 *Weathered Sage\**

**COVERAGE RATE FOR COLOR HARDENER:** Coverage rates vary with intended use and application. LITHOCHROME Color Hardener should be applied at a rate of 50 lb (1 bag) per 100 ft<sup>2</sup> (2.5 kg/m<sup>2</sup>), except where indicated by an asterisk (\*).

\*Denotes colors requiring a higher coverage rate, where Scofield recommends 90-120 lb per 100 ft<sup>2</sup> (4.5-6.0 kg/m<sup>2</sup>). See reverse for more information.

+SS = Check current market price.

Colors are approximate and best viewed in daylight. Colors shown represent the use of LITHOCHROME Color Hardener with a flat-troweled finish which has been cured with color-matched LITHOCHROME Colorwax or COLORCURE Concrete Sealer.